

T8 LED nature - pink - g13

T8 LED TUBE 24W Pink SMD 1500mm
G13

Cod: **5455882**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



Exempt
Product exempt from energy
labelling



II
Protection class II



CRI >85
Colour rendering index >85



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5455882 | Category: LED tubes | Model: T8 LED nature - pink - g13 | Product description: T8 LED TUBE 24W Pink SMD 1500mm G13 | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 3700K | Color render index (CRI): > 85 | MacAdam (SDCM): < 6 | Lumen output (lm): 2040 | Beam angle: 160° | Photobiological risk: RG0 (exempt) | LED Lifetime: 25.000 h | Maintenance factor: 70% | Number of switching cycles: > 12.500 | Energy efficiency class: Exempt | Diameter (mm): 26 | Length (mm): 1500 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Rose | Body material: Technopolymer | Maximal working temperature: -25° C | Minimal working temperature: +40° C | Nominal power (W): 24 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 10 |

Lighting data

| | | | |
|--------------------------|-------|----------------------------|--------------|
| MacAdam (SDCM) | < 1 | Photobiological risk | RG0 (exempt) |
| Ignition time | 1,0 | LED Lifetime | 25.000 h |
| Color temperature (CCT) | 3700K | Maintenance factor | 70% |
| Color render index (CRI) | > 85 | Number of switching cycles | > 12.500 |
| MacAdam (SDCM) | < 6 | Energy efficiency class | Exempt |
| Lumen output (lm) | 2040 | | |
| Beam angle | 160° | | |

Mechanical data

| | | | |
|---------------|------|------------------|---------------|
| Diameter (mm) | 26 | IP rating | IP 20 |
| Length (mm) | 1500 | Finishing colour | Rose |
| Lamp holder | G13 | Body material | Technopolymer |

Electrical data

| | | | |
|-------------------|--------------|----------------------|----|
| Nominal power (W) | 2,4 | Dimmable | No |
| Power factor | 0,9 | Quantity per package | 10 |
| Power supply | 230V 50/60Hz | | |
| Insulation class | II | | |