

T8 LED aluminum - g13

T8 LED TUBE 18W 4000K SMD G13
1213mm

Cod: **5456032**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



F
Energy efficiency class F



II
Protection class II



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456032 | Category: LED tubes | Model: T8 LED aluminum - g13 | Product description: T8 LED TUBE 18W 4000K SMD G13 1213mm | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1800 | Beam angle: 250° | Photobiological risk: RG0 (exempt) | LED Lifetime: 25.000 h | Maintenance factor: 70% | Number of switching cycles: > 12.500 | Energy efficiency class: F | Diameter (mm): 28 | Length (mm): 1213 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Opal White | Body material: Aluminum | Maximal working temperature: -20° C | Minimal working temperature: +45° C | Nominal power (W): 17,5 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 12

Lighting data

MacAdam (SDCM)	< 1	Photobiological risk	RG0 (exempt)
Ignition time	1,0	LED Lifetime	25.000 h
Color temperature (CCT)	4000K	Maintenance factor	70%
Color render index (CRI)	> 80	Number of switching cycles	> 12.500
MacAdam (SDCM)	< 6	Energy efficiency class	F
Lumen output (lm)	1800		
Beam angle	250°		

Mechanical data

Diameter (mm)	28	IP rating	IP 20
Length (mm)	1213	Finishing colour	Opal White
Lamp holder	G13	Body material	Aluminum

Electrical data

Nominal power (W)	17,5	Dimmable	No
Power factor	0,9	Quantity per package	12
Power supply	230V 50/60Hz		
Insulation class	II		