

T8 LED hp aluminum - g13

T8 LED TUBE newHP 6,7W 4000K SMD
LED 600mm

Cod: **5456144**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



C
Energy efficiency class C



II
Protection class II



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456144 | Category: LED tubes | Model: T8 LED hp aluminum - g13 | Product description: T8 LED TUBE newHP 6,7W 4000K SMD LED 600mm | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1100 | Beam angle: 250° | Photobiological risk: RG0 (exempt) | LED Lifetime: 50.000 h | Maintenance factor: 70% | Number of switching cycles: > 25.000 | Energy efficiency class: C | Diameter (mm): 28 | Length (mm): 604 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Opal White | Body material: Aluminum | Maximal working temperature: -20° C | Minimal working temperature: +45° C | Nominal power (W): 6,5 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 12 |

Lighting data

| | | | |
|--------------------------|-------|----------------------------|--------------|
| MacAdam (SDCM) | < 1 | Photobiological risk | RG0 (exempt) |
| Ignition time | 1,0 | LED Lifetime | 50.000 h |
| Color temperature (CCT) | 4000K | Maintenance factor | 70% |
| Color render index (CRI) | > 80 | Number of switching cycles | > 25.000 |
| MacAdam (SDCM) | < 6 | Energy efficiency class | C |
| Lumen output (lm) | 1100 | | |
| Beam angle | 250° | | |

Mechanical data

| | | | |
|---------------|-----|------------------|------------|
| Diameter (mm) | 28 | IP rating | IP 20 |
| Length (mm) | 604 | Finishing colour | Opal White |
| Lamp holder | G13 | Body material | Aluminum |

Electrical data

| | | | |
|-------------------|--------------|----------------------|----|
| Nominal power (W) | 6.5 | Dimmable | No |
| Power factor | 0,9 | Quantity per package | 12 |
| Power supply | 230V 50/60Hz | | |
| Insulation class | II | | |