



LED R50 - E14

LED BULB R50 230V E14 4W 3000K 110°
Erp

Cod: **5456152**



E14
Lamp holder: E14



IP20
Protected from solid bodies larger than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: 5456152 | Category: LED lamps | Model: LED R50 - E14 | Product description: LED BULB R50 230V E14 4W 3000K 110° Erp | Warm-up time: 1 | Ignition time: 0,5 | Color temperature (CCT): 3000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 450 | Beam angle: 110° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 50 | Height (mm): 85 | Lamp holder: E14 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 4 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

Lighting data

| | | | |
|--------------------------|-------|----------------------------|----------|
| MacAdam (SDCM) | < 1 | LED Lifetime | 15.000 h |
| Ignition time | 0,5 | Maintenance factor | 70% |
| Color temperature (CCT) | 3000K | Number of switching cycles | > 7.500 |
| Color render index (CRI) | > 80 | Energy efficiency class | E |
| MacAdam (SDCM) | < 6 | | |
| Lumen output (lm) | 450 | | |
| Beam angle | 110° | | |

Mechanical data

| | | | |
|---------------|-----|-------------------|---------------|
| Diameter (mm) | 50 | IP rating | IP 20 |
| Height (mm) | 85 | Finishing colour | Opal |
| Lamp holder | E14 | Diffuser material | Technopolymer |

Electrical data

| | | | |
|-------------------|--------------|----------------------|----|
| Nominal power (W) | 4 | Quantity per package | 10 |
| Power factor | 0,5 | | |
| Power supply | 230V 50/60Hz | | |
| Dimmable | No | | |