



LED AR111- G53 / direct and alternating current

LED BULB AR111 G53 12V 13W 3000K 40°
- DIMMABLE Erp

Cod: **5456233**



G53
Lamp holder: G53



IP20
Protected from solid bodies larger
than 12 mm



G
Energy efficiency class



CRI >80
Colour rendering index >80



Dimmable
Dimmable product



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456233 | Category: LED lamps | Model: LED AR111- G53 / direct and alternating current | Product description: LED BULB AR111 G53 12V 13W 3000K 40° - DIMMABLE Erp | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 3000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 950 | Beam angle: 40° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: G | Diameter (mm): 111 | Height (mm): 61 | Lamp holder: G53 | IP rating: IP 20 | Finishing colour: Clear | Nominal power (W): 13 | Power supply: 12V 50Hz | Dimmable: Yes | Quantity per package: 20 |

Lighting data

MacAdam (SDCM)	< 1	LED Lifetime	15.000 h
Ignition time	0,5	Maintenance factor	70%
Color temperature (CCT)	3000K	Number of switching cycles	> 7.500
Color render index (CRI)	> 80	Energy efficiency class	G
MacAdam (SDCM)	< 6		
Lumen output (lm)	950		
Beam angle	40°		

Mechanical data

Diameter (mm)	111	IP rating	IP 20
Height (mm)	61	Finishing colour	Clear
Lamp holder	G53		

Electrical data

Nominal power (W)	13	Quantity per package	20
Power supply	12V 50Hz		
Dimmable	Yes		