

# LED G9

G9 LED BULB 230V 4,2W 3000K  
Erp/EMC

Cod: **5456270**



G9  
Lamp holder: G9



IP20  
Protected from solid bodies larger than 12 mm



E  
Energy efficiency class E



CRI >80  
Colour rendering index >80



ReeR warranty  
ReeR guarantees the product for a time duration of 3 years



## Technical description

Product code: 5456270 | Category: LED lamps | Model: LED G9 | Product description: G9 LED BULB 230V 4,2W 3000K Erp/EMC | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 3000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 470 | Beam angle: 330° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 16 | Height (mm): 62 | Lamp holder: G9 | IP rating: IP 20 | Finishing colour: Clear | Nominal power (W): 4,2 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

### Lighting data

|                          |       |                            |          |
|--------------------------|-------|----------------------------|----------|
| MacAdam (SDCM)           | < 1   | LED Lifetime               | 15.000 h |
| Ignition time            | 0,5   | Maintenance factor         | 70%      |
| Color temperature (CCT)  | 3000K | Number of switching cycles | > 7.500  |
| Color render index (CRI) | > 80  | Energy efficiency class    | E        |
| MacAdam (SDCM)           | < 6   |                            |          |
| Lumen output (lm)        | 470   |                            |          |
| Beam angle               | 330°  |                            |          |

### Mechanical data

|               |    |                  |       |
|---------------|----|------------------|-------|
| Diameter (mm) | 16 | IP rating        | IP 20 |
| Height (mm)   | 62 | Finishing colour | Clear |
| Lamp holder   | G9 |                  |       |

### Electrical data

|                   |              |                      |    |
|-------------------|--------------|----------------------|----|
| Nominal power (W) | 4,2          | Quantity per package | 10 |
| Power factor      | 0,5          |                      |    |
| Power supply      | 230V 50/60Hz |                      |    |
| Dimmable          | No           |                      |    |