

Unica EVO mono 1500mm



UNICA EVO MONO 28W IP65 1500mm
4000K

Cod: **6360980**



IP65
Dustproof and protected against
water jets



I
Protection class I



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 6360980 | Category: Outdoor luminaires | Model: Unica EVO mono 1500mm | Product description: UNICA EVO MONO 28W IP65 1500mm 4000K | Source type: SMD | Number of LEDs: 144 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 4 | Lumen output (lm): 3200 | Beam angle: 120° | Photobiological risk: RG0 (exempt) | LED Lifetime: 50.000 h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): E | Width (mm): 150 | Length (mm): 1500 | Height (mm): 58 | Weight (g): 1450 | IP rating: IP 65 | IK rating: IK 08 | Finishing colour: Grey | Body material: PC (polycarbonate) | Diffuser material: PC (polycarbonate) | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 28 | Power factor: > 0,9 | Power supply: 230V 50/60Hz | Ballast: Included | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD	Beam angle	120°
Number of LEDs	144	Photobiological risk	RG0 (exempt)
Color temperature (CCT)	4000K	LED Lifetime	50.000 h
Color render index (CRI)	> 80	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): E
MacAdam (SDCM)	< 4		
Lumen output (lm)	3200		


Mechanical data

Width (mm)	150	IK rating	IK 08
Length (mm)	1500	Finishing colour	Grey
Height (mm)	58	Body material	PC (polycarbonate)
Weight (g)	1450	Diffuser material	PC (polycarbonate)
IP rating	IP 65		

Electrical data

Nominal power (W)	28	Insulation class	I
Power factor	0,9	Dimmable	No
Power supply	230V 50/60Hz		
Ballast	Included		

Photometry



Technical drawing

