



Unica EVO

emergency 1500mm

UNICA EVO EMERGENCY 3h 48W
1200mm

Cod: **6360991**



IP65

Dustproof and protected against water jets



I

Protection class I



CRI >80

Colour rendering index >80



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: 6360991 | Category: Outdoor luminaires | Model: Unica EVO emergency 1500mm | Product description: UNICA EVO EMERGENCY 3h 48W 1200mm | Source type: SMD 2835 | Number of LEDs: 248 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 5500 | Beam angle: 120° | Photobiological risk: RG0 (exempt) | LED Lifetime: 30.000 h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): E | Width (mm): 92 | Length (mm): 1200 | Height (mm): 60 | Weight (g): 2200 | IP rating: IP 65 | IK rating: IK 08 | Finishing colour: Grey | Body material: PC (polycarbonate) | Diffuser material: PC (polycarbonate) | Maximal working temperature: -10° C | Minimal working temperature: +40° C | Nominal power (W): 48 | Power factor: > 0,9 | Power supply: 230V 50/60Hz | Ballast: Included | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD 2835	Beam angle	120°
Number of LEDs	248	Photobiological risk	RG0 (exempt)
Color temperature (CCT)	4000K	LED Lifetime	30.000 h
Color render index (CRI)	> 80	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): E
MacAdam (SDCM)	< 6		
Lumen output (lm)	5500		


Mechanical data

Width (mm)	92	IK rating	IK 08
Length (mm)	1200	Finishing colour	Grey
Height (mm)	60	Body material	PC (polycarbonate)
Weight (g)	2200	Diffuser material	PC (polycarbonate)
IP rating	IP 65		

Electrical data

Nominal power (W)	48	Insulation class	I
Power factor	0,9	Dimmable	No
Power supply	230V 50/60Hz		
Ballast	Included		

Photometry



Technical drawing

