



# Street Star V2 60W

STREET STAR V2 60W 4000K IP65 230V

Cod: **6361172**



IP65  
Dustproof and protected against water jets



II  
Protection class II



ReeR warranty  
ReeR guarantees the product for a time duration of 3 years



## Technical description

Product code: 6361172 | Category: Outdoor luminaires | Model: Street Star V2 60W | Product description: STREET STAR V2 60W 4000K IP65 230V | Source type: SMD 3030 | Color temperature (CCT): 4000K | Color render index (CRI): > 70 | MacAdam (SDCM): < 6 | Lumen output (lm): 9600 | Beam angle: Asymmetric 45° x 120° | Photobiological risk: RG1 (low risk) | LED Lifetime: 30.000 h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): D | Width (mm): 200 | Length (mm): 565 | Height (mm): 89 | Weight (g): 4500 | IP rating: IP 65 | IK rating: IK 08 | Finishing colour: Grey RAL9006 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -30° C | Minimal working temperature: +50° C | Nominal power (W): 60 | Power factor: > 0,90 | Power supply: 100-277V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

## Lighting data

Source type	SMD 3030
Color temperature (CCT)	4000K
Color render index (CRI)	> 70
MacAdam (SDCM)	< 6
Lumen output (lm)	9600
Beam angle	Asymmetric 45° x 120°

Photobiological risk	RG1 (low risk)
LED Lifetime	30.000 h
Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): D

## Mechanical data

Width (mm)	200
Length (mm)	565
Height (mm)	89
Weight (g)	4500
IP rating	IP 65

IK rating	IK 08
Finishing colour	Grey RAL9006
Type of finishing	Polyester powder coated
Body material	Aluminum
Diffuser material	Tempered glass

## Electrical data

Nominal power (W)	60
Power factor	> 0,90
Power supply	100-277V 50/60Hz
Ballast	Integrated

Insulation class	II
Dimmable	No

## Photometry

