



Street Star V2 150W

STREET STAR V2 150W 4000K IP65 230V

Cod: **6361176**



IP65
Dustproof and protected against water jets



II
Protection class II



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: 6361176 | Category: Outdoor luminaires | Model: Street Star V2 150W | Product description: STREET STAR V2 150W 4000K IP65 230V | Source type: SMD 3030 | Color temperature (CCT): 4000K | Color render index (CRI): > 70 | MacAdam (SDCM): < 6 | Lumen output (lm): 24000 | Beam angle: Asymmetric 45° x 120° | Photobiological risk: RG1 (low risk) | LED Lifetime: 30.000 h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): D | Width (mm): 260 | Length (mm): 680 | Height (mm): 89 | Weight (g): 6000 | IP rating: IP 65 | IK rating: IK 08 | Finishing colour: Grey RAL9006 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -30° C | Minimal working temperature: +50° C | Nominal power (W): 150 | Power factor: > 0,90 | Power supply: 100-277V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

Lighting data

Source type	SMD 3030	Photobiological risk	RG1 (low risk)
Color temperature (CCT)	4000K	LED Lifetime	30.000 h
Color render index (CRI)	> 70	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): D
MacAdam (SDCM)	< 6		
Lumen output (lm)	24000		
Beam angle	Asymmetric 45° x 120°		

Mechanical data

Width (mm)	260	IK rating	IK 08
Length (mm)	680	Finishing colour	Grey RAL9006
Height (mm)	89	Type of finishing	Polyester powder coated
Weight (g)	6000	Body material	Aluminum
IP rating	IP 65	Diffuser material	Tempered glass

Electrical data

Nominal power (W)	150	Insulation class	II
Power factor	> 0,90	Dimmable	No
Power supply	100-277V 50/60Hz		
Ballast	Integrated		

Photometry

