



Globe 20W

GLOBO 20W 3000K 36° White RAL9003

Cod: MIC0062



IP20
Protected from solid bodies larger than 12 mm



II
Protection class II



CRI >90
Colour rendering index >90



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MIC0062 | Category: Indoor luminaires | Model: Globe 20W | Product description: GLOBE 20W 3000K 36° White RAL9003 | Color temperature (CCT): 3000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 1654 | Beam angle: 36° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Diameter (mm): 112 | Height (mm): 112 | Recess hole (mm): Ø 105 | Weight (g): 500 | IP rating: IP 20 | Finishing colour: White RAL9003 | Body material: Aluminum and PC | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 20 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz 500mA | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

Color temperature (CCT)	3000K
Color render index (CRI)	> 90
MacAdam (SDCM)	< 3
Lumen output (lm)	1654
Beam angle	36°

Photobiological risk	RG2 (moderate risk)
LED Lifetime	50.000 h

Mechanical data

Diameter (mm)	112
Height (mm)	112
Recess hole (mm)	Ø105
Weight (g)	500

IP rating	IP 20
Finishing colour	White RAL9003
Body material	Aluminum and PC

Electrical data

Nominal power (W)	20
Power factor	0,9
Power supply	220/240V 50/60Hz 500mA
Ballast	Included

Insulation class	II
Dimmable	No

