

Globe 8,5W

GLOBO 8,5W 4000K 24° White RAL9003

Cod: MIC0068



IP20

Protected from solid bodies larger than 12 mm



II

Protection class II



CRI >90

Colour rendering index >90



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MIC0068 | Category: Indoor luminaires | Model: Globe 8,5W | Product description: GLOBE 8,5W 4000K 24° White RAL9003 | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 525 | Beam angle: 24° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Diameter (mm): 83 | Height (mm): 81 | Recess hole (mm): Ø 75 | Weight (g): 200 | IP rating: IP 20 | Finishing colour: White RAL9003 | Body material: Aluminum and PC | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 8,5 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz 200mA | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

Color temperature (CCT)	4000K
-------------------------	-------

Color render index (CRI)	> 90
--------------------------	------

MacAdam (SDCM)	< 3
----------------	-----

Lumen output (lm)	525
-------------------	-----

Beam angle	24°
------------	-----

Photobiological risk	RG2 (moderate risk)
----------------------	---------------------

LED Lifetime	50.000 h
--------------	----------

Mechanical data

Diameter (mm)	83
---------------	----

Height (mm)	81
-------------	----

Recess hole (mm)	Ø 75
------------------	------

Weight (g)	200
------------	-----

IP rating	IP 20
-----------	-------

Finishing colour	White RAL9003
------------------	---------------

Body material	Aluminum and PC
---------------	-----------------

Electrical data

Nominal power (W)	8.5
-------------------	-----

Power factor	0,9
--------------	-----

Power supply	220/240V 50/60Hz 200mA
--------------	------------------------

Ballast	Included
---------	----------

Insulation class	II
------------------	----

Dimmable	No
----------	----

Photometry

