



Globe 29W

GLOBO 29W 4000K 36 White RAL9003

Cod: MIC0075



IP20
Protected from solid bodies larger than 12 mm



II
Protection class II



CRI >90
Colour rendering index >90



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MIC0075 | Category: Indoor luminaires | Model: Globe 29W | Product description: GLOBE 29W 4000K 36 White RAL9003 | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 2315 | Beam angle: 36° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Diameter (mm): 125 | Height (mm): 122 | Recess hole (mm): Ø 115 | Weight (g): 670 | IP rating: IP 20 | Finishing colour: White RAL9003 | Body material: Aluminum and PC | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 29 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz 700mA | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

Color temperature (CCT)	4000K	Photobiological risk	RG2 (moderate risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	2315		
Beam angle	36°		


Mechanical data

Diameter (mm)	125	IP rating	IP 20
Height (mm)	122	Finishing colour	White RAL9003
Recess hole (mm)	Ø 115	Body material	Aluminum and PC
Weight (g)	670		

Electrical data

Nominal power (W)	29	Insulation class	II
Power factor	0,9	Dimmable	No
Power supply	220/240V 50/60Hz 700mA		
Ballast	Included		

Photometry



Technical drawing

