



Teatro square 8,5W

TEATRO SQUARE 8,5W 3000K 30° black frame

Cod: MIC0105



IP20
Protected from solid bodies larger than 12 mm



II
Protection class II



CRI >90
Colour rendering index >90



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MIC0105 | Category: Indoor luminaires | Model: Teatro square 8,5W | Product description: TEATRO SQUARE 8,5W 3000K 30° black frame | Source type: COB | Color temperature (CCT): 3000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 648 | Beam angle: 30° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Width (mm): 67 | Length (mm): 67 | Height (mm): 78 | Recess hole (mm): 55 x 55 | Weight (g): 180 | IP rating: IP 20 | Finishing colour: White RAL9003 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: PC (polycarbonate) | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 8,5 | Power factor: > 0,5 | Power supply: 220/240V 50/60Hz | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

Source type	COB	Beam angle	30°
Color temperature (CCT)	3000K	Photobiological risk	RG2 (moderate risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	648		

Mechanical data

Width (mm)	67	IP rating	IP 20
Length (mm)	67	Finishing colour	Black
Height (mm)	78	Type of finishing	Polyester powder coated
Recess hole (mm)	55 x 55	Body material	Aluminum
Weight (g)	180	Diffuser material	PC (polycarbonate)

Electrical data

Nominal power (W)	8.5	Insulation class	II
Power factor	0,5	Dimmable	No
Power supply	220/240V 50/60Hz		
Ballast	Included		

Photometry



Technical drawing

