



Teatro square 20W

TEATRO SQUARE 20W 3000K 30° white frame

Cod: **MIC0154**



IP20

Protected from solid bodies larger than 12 mm



II

Protection class II



CRI >90

Colour rendering index >90



Reer warranty

Reer guarantees the product for a time duration of 3 years



Technical description

Product code: MIC0154 | Category: Indoor luminaires | Model: Teatro square 20W | Product description: TEATRO SQUARE 20W 3000K 30° white frame | Source type: COB | Color temperature (CCT): 3000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 1820 | Beam angle: 30° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Width (mm): 110 | Length (mm): 110 | Height (mm): 117 | Recess hole (mm): 95 x 95 | Weight (g): 480 | IP rating: IP 20 | Finishing colour: White RAL9003 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: PC (polycarbonate) | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 20 | Power factor: > 0,7 | Power supply: 220/240V 50/60Hz | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

Source type	COB	Beam angle	30°
Color temperature (CCT)	3000K	Photobiological risk	RG2 (moderate risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	1820		

Mechanical data

Width (mm)	110	IP rating	IP 20
Length (mm)	110	Finishing colour	White
Height (mm)	117	Type of finishing	Polyester powder coated
Recess hole (mm)	95 x 95	Body material	Aluminum
Weight (g)	480	Diffuser material	PC (polycarbonate)

Electrical data

Nominal power (W)	20	Insulation class	II
Power factor	0,7	Dimmable	No
Power supply	220/240V 50/60Hz		
Ballast	Included		

Photometry



Technical drawing

