



# Teatro square 33W

TEATRO SQUARE 33W 3000K 30° nickel frame

Cod: **MIC0320**



IP20

Protected from solid bodies larger than 12 mm



II

Protection class II



CRI >90

Colour rendering index >90



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



## Technical description

Product code: MIC0320 | Category: Indoor luminaires | Model: Teatro square 33W | Product description: TEATRO SQUARE 33W 3000K 30° nickel frame | Source type: COB | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 2404 | Beam angle: 45° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Width (mm): 132 | Length (mm): 132 | Height (mm): 135 | Recess hole (mm): 115 x 115 | Weight (g): 700 | IP rating: IP 20 | Finishing colour: White RAL9003 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: PC (polycarbonate) | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 33 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Included | Insulation class: II | Dimmable: No |

### Lighting data

Source type	COB	Beam angle	45°
Color temperature (CCT)	4000K	Photobiological risk	RG2 (moderate risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	2404		


### Mechanical data

Width (mm)	132	IP rating	IP 20
Length (mm)	132	Finishing colour	Nickel
Height (mm)	135	Type of finishing	Polyester powder coated
Recess hole (mm)	115 x 115	Body material	Aluminum
Weight (g)	700	Diffuser material	PC (polycarbonate)

### Electrical data

Nominal power (W)	33	Insulation class	II
Power factor	0,9	Dimmable	No
Power supply	220/240V 50/60Hz		
Ballast	Included		

## Photometry



## Technical drawing

