



# Effetto 23W

EFFETTO 4000K 23W 40° White  
(600mA)

Cod: **MTK0011**



IP20

Protected from solid bodies larger than 12 mm



II

Protection class II



CRI >90

Colour rendering index >90



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



## Technical description

Product code: MTK0011 | Category: Indoor luminaires | Model: Effetto 23W | Product description: EFFETTO 4000K 23W 40° White (600mA) | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 2482 | Beam angle: 40° | Photobiological risk: RG1 (low risk) | LED Lifetime: 50.000 h | Diameter (mm): 95 | Height (mm): 113 | Weight (g): 1200 | IP rating: IP 20 | Finishing colour: White RAL9016 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 23 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

## Lighting data

Color temperature (CCT)	4000K	Photobiological risk	RG1 (low risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	2482		
Beam angle	40°		


## Mechanical data

Diameter (mm)	95	Finishing colour	White RAL9016
Height (mm)	113	Type of finishing	Polyester powder coated
Weight (g)	1200	Body material	Aluminum
IP rating	IP 20	Diffuser material	Tempered glass

## Electrical data

Nominal power (W)	2,3	Insulation class	II
Power factor	0,9	Dimmable	No
Power supply	220/240V 50/60Hz		
Ballast	Integrated		

## Photometry



## Technical drawing

