



Effetto 28W

EFFETTO 4000K 28W 60° Black (700mA)

Cod: **MTK0032**



IP20

Protected from solid bodies larger than 12 mm



II

Protection class II



CRI >90

Colour rendering index >90



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MTK0032 | Category: Indoor luminaires | Model: Effetto 28W | Product description: EFFETTO 4000K 28W 60° Black (700mA) | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 2852 | Beam angle: 60° | Photobiological risk: RG1 (low risk) | LED Lifetime: 50.000 h | Diameter (mm): 95 | Height (mm): 113 | Weight (g): 1200 | IP rating: IP 20 | Finishing colour: Black RAL9004 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 28 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

Lighting data

Color temperature (CCT)	4000K	Photobiological risk	RG1 (low risk)
Color render index (CRI)	> 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3		
Lumen output (lm)	2852		
Beam angle	60°		

Mechanical data

Diameter (mm)	95	Finishing colour	Black RAL9004
Height (mm)	113	Type of finishing	Polyester powder coated
Weight (g)	1200	Body material	Aluminum
IP rating	IP 20	Diffuser material	Tempered glass

Electrical data

Nominal power (W)	28	Insulation class	II
Power factor	0,9	Dimmable	No
Power supply	220/240V 50/60Hz		
Ballast	Integrated		

Photometry



Technical drawing

