



# Risalto 32W

RISALTO 4000K 32W 16° White (850mA)

Cod: **MTK0065**



IP20  
Protected from solid bodies larger than 12 mm



I  
Protection class I



CRI >90  
Colour rendering index >90



ReeR warranty  
ReeR guarantees the product for a time duration of 3 years



## Technical description

Product code: MTK0065 | Category: Indoor luminaires | Model: Risalto 32W | Product description: RISALTO 4000K 32W 16° White (850mA) | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 3210 | Beam angle: 16° | Photobiological risk: RG1 (low risk) | LED Lifetime: 50.000 h | Diameter (mm): 95 | Height (mm): 113 | Weight (g): 1200 | IP rating: IP 20 | Finishing colour: White RAL9016 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 32 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

## Lighting data

|                          |       |                      |                |
|--------------------------|-------|----------------------|----------------|
| Color temperature (CCT)  | 4000K | Photobiological risk | RG1 (low risk) |
| Color render index (CRI) | > 90  | LED Lifetime         | 50.000 h       |
| MacAdam (SDCM)           | < 3   |                      |                |
| Lumen output (lm)        | 3210  |                      |                |
| Beam angle               | 16°   |                      |                |

## Mechanical data

|               |       |                   |                         |
|---------------|-------|-------------------|-------------------------|
| Diameter (mm) | 95    | Finishing colour  | White RAL9016           |
| Height (mm)   | 113   | Type of finishing | Polyester powder coated |
| Weight (g)    | 1200  | Body material     | Aluminum                |
| IP rating     | IP 20 | Diffuser material | Tempered glass          |

## Electrical data

|                   |                  |                  |    |
|-------------------|------------------|------------------|----|
| Nominal power (W) | 32               | Insulation class | I  |
| Power factor      | 0,9              | Dimmable         | No |
| Power supply      | 220/240V 50/60Hz |                  |    |
| Ballast           | Integrated       |                  |    |

## Photometry

