



Risalto 38W

RISALTO 4000K 38W 40° Black (950mA)

Cod: **MTK0087**



IP20
Protected from solid bodies larger than 12 mm



I
Protection class I



CRI >90
Colour rendering index >90



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MTK0087 | Category: Indoor luminaires | Model: Risalto 38W | Product description: RISALTO 4000K 38W 40° Black (950mA) | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 3724 | Beam angle: 40° | Photobiological risk: RG1 (low risk) | LED Lifetime: 50.000 h | Diameter (mm): 95 | Height (mm): 113 | Weight (g): 1200 | IP rating: IP 20 | Finishing colour: Black RAL9004 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 38 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Color temperature (CCT)	4000K
Color render index (CRI)	> 90
MacAdam (SDCM)	< 3
Lumen output (lm)	3724
Beam angle	40°

Photobiological risk	RG1 (low risk)
LED Lifetime	50.000 h

Mechanical data

Diameter (mm)	95
Height (mm)	113
Weight (g)	1200
IP rating	IP 20

Finishing colour	Black RAL9004
Type of finishing	Polyester powder coated
Body material	Aluminum
Diffuser material	Tempered glass

Electrical data

Nominal power (W)	3,8
Power factor	0,9
Power supply	220/240V 50/60Hz
Ballast	Integrated

Insulation class	I
Dimmable	No

Photometry

